2.54mm Crimp Terminal

TERMINAL PART NO:3716PS-2

• Material: Phos. Bronze

• Wire Range: AWG 22-24,26-30,and 32-36

• Three plating specs

• Available on reels or loose

• Dual beam. Fully enclosed box contact with locking lance

• Mates with 0.64mm Pins

• Accepts Housing: 2546H

SPECIFICATIONS

• Current rating: 3A AC, DC

• Voltage rating: 250V AC, DC

• Temperature range: -25°C~+85°C

(Including temperature rise)


• Contact resistance: Initial value/10m Ω max.


After environmental


Testing/20m Ω max


• Insulation resistance: 1,000m Ω min

• Withstand voltage: 1,000V AC/minute









HO TIEN PRECISION INDUSTRY CO., LTD. 合田精密工業股份有限公司

| RECORD OF REVISION / 修定內容 | REV.BY / 修定者 | REV. DATE / 修定日期 | PART NO. / 型號 | | 3716PS-2 | | APPROVED BY / 核淮 | | |
|---------------------------|--------------|------------------|------------------|--------|---------------|-----|---------------------|--|--|
| | | | METERIAI | L / 材質 | Phos. Bronze | | CHECKED BY / 審查 | | |
| | | | TREATMENT / 表面處理 | | Tin 60µ"/Gold | | DRAWN/製圖 | | |
| | | | CUSTOMER / 客戶名稱 | | | | DATE/製圖日期 | | |
| | | | UNIT / 單位 | mm | SCALE / 比例 | 1/2 | DRAWING TYPE / 圖面種類 | | |