



1.材質=P.B.T.加30%玻籤普通

1.材質=P.B.T.加30%玻籤無鹵

POSITION	"A"	"B"	POSITION	"A"	"B"
			16 P	38.10	40.64
2 P	2.54	5.08	17 P	40.64	43.18
3 P	5.08	7.62	18 P	43.18	45.72
4 P	7.62	10.16	19 P	45.72	48.26
5 P	10.16	12.70	20 P	48.26	50.80
6 P	12.70	15.24	21 P	50.80	53.34
7 P	15.24	17.78	22 P	53.34	55.88
8 P	17.78	20.32	23 P	55.88	58.42
9 P	20.32	22.86	24 P	58.42	60.96
10 P	22.86	25.40	25 P	60.96	63.50
11 P	25.40	27.94	26 P	63.50	66.04
12 P	27.94	30.48	27 P	66.04	68.58
13 P	30.48	33.02	28 P	68.58	71.12
14 P	33.02	35.56	29 P	71.12	73.66
15 P	35.56	38.10	30 P	73.66	76.20



HO TIEN PRECISION INDUSTRY CO., LTD.

和田精密股份有限公司

RECORD OF REVISION/ 修定內容	REV.BY/ 修定者	REV.DATE/ 修定日期	PART NO./ 料號	3815H		APPROVED BY/ 核准	
			MATERIAL/ 材質			CHECKED BY/ 審查	
			TREATMENT/ 表面處理			DRAWN/ 製圖	STONE
			CUSTOMER/ 客戶品名			DATE/ 製圖日期	2012-11-09
			UNIT/ 單位	mm	SCALE/ 比例	4:1	DRAWING TYPE/ 圖面種類