



| POSITION | "A" | "B" | POSITION | "A" | "B" |
|----------|-------|-------|----------|-------|-------|
| 8 P | 3.81 | 6.15 | 56 P | 34.29 | 36.63 |
| 10 P | 5.08 | 7.42 | 58 P | 35.56 | 37.90 |
| 12 P | 6.35 | 8.69 | 60 P | 36.83 | 39.17 |
| 14 P | 7.62 | 9.96 | 62 P | 38.10 | 40.44 |
| 16 P | 8.89 | 11.23 | 64 P | 39.37 | 41.71 |
| 18 P | 10.16 | 12.50 | 66 P | 40.64 | 42.98 |
| 20 P | 11.43 | 13.77 | 68 P | 41.91 | 44.25 |
| 22 P | 12.7 | 15.04 | 70 P | 43.18 | 45.52 |
| 24 P | 13.97 | 16.31 | 72 P | 44.45 | 46.79 |
| 26 P | 15.24 | 17.58 | 74 P | 45.72 | 48.06 |
| 28 P | 16.51 | 18.85 | 76 P | 46.99 | 49.33 |
| 30 P | 17.78 | 20.12 | 78 P | 48.26 | 50.60 |
| 32 P | 19.05 | 21.39 | 80 P | 49.53 | 51.87 |
| 34 P | 20.32 | 22.66 | 82 P | 50.8 | 53.14 |
| 36 P | 21.59 | 23.93 | 84 P | 52.07 | 54.41 |
| 38 P | 22.86 | 25.20 | 86 P | 53.34 | 55.68 |
| 40 P | 24.13 | 26.47 | 88 P | 54.61 | 56.95 |
| 42 P | 25.4 | 27.74 | 90 P | 55.88 | 58.22 |
| 44 P | 26.67 | 29.01 | 92 P | 57.15 | 59.49 |
| 46 P | 27.94 | 30.28 | 94 P | 58.42 | 60.76 |
| 48 P | 29.21 | 31.56 | 96 P | 59.69 | 62.03 |
| 50 P | 30.48 | 32.82 | 98 P | 60.96 | 63.30 |
| 52 P | 31.75 | 34.09 | 100 P | 62.23 | 64.57 |
| 54 P | 33.02 | 35.36 | | | |


 HO TIEN PRECISION INDUSTRY CO., LTD.
 和田精密股份有限公司

| | | | | | | |
|--------------------------|-------------|----------------|-----------------|---------------|--------------------|------------|
| RECORD OF REVISION/ 修定内容 | REV.BY/ 修定者 | REV.DATE/ 修定日期 | PART NO./ 料號 | 3872H | APPROVED BY/ 核准 | |
| | | | MATERIAL/ 材質 | PA66 UL 94V-0 | CHECKED BY/ 審查 | |
| | | | TREATMENT/ 表面處理 | | DRAWN/ 製圖 | STONE |
| | | | CUSTOMER/ 客戶品名 | | DATE/ 製圖日期 | 2016-10-19 |
| | | | UNIT/ 單位 | mm | SCALE/ 比例 | 1:1 |
| | | | | | DRAWING TYPE/ 圖面種類 | |