



POSITION	"A"	"B"	POSITION	"A"	"B"
10 P	5.08	7.42	56 P	34.29	36.63
12 P	6.35	8.69	58 P	35.56	37.90
14 P	7.62	9.96	60 P	36.83	39.17
16 P	8.89	11.23	62 P	38.10	40.44
18 P	10.16	12.50	64 P	39.37	41.71
20 P	11.43	13.77	66 P	40.64	42.98
22 P	12.7	15.04	68 P	41.91	44.25
24 P	13.97	16.31	70 P	43.18	45.52
26 P	15.24	17.58	72 P	44.45	46.79
28 P	16.51	18.85	74 P	45.72	48.06
30 P	17.78	20.12	76 P	46.99	49.33
32 P	19.05	21.39	78 P	48.26	50.60
34 P	20.32	22.66	80 P	49.53	51.87
36 P	21.59	23.93	82 P	50.8	53.14
38 P	22.86	25.20	84 P	52.07	54.41
40 P	24.13	26.47	86 P	53.34	55.68
42 P	25.4	27.74	88 P	54.61	56.95
44 P	26.67	29.01	90 P	55.88	58.22
46 P	27.94	30.28	92 P	57.15	59.49
48 P	29.21	31.56	94 P	58.42	60.76
50 P	30.48	32.82	96 P	59.69	62.03
52 P	31.75	34.09	98 P	60.96	63.30
54 P	33.02	35.36	100 P	62.23	64.57



HO TIEN PRECISION INDUSTRY CO., LTD.

和田精密股份有限公司

RECORD OF REVISION/ 修定内容	REV.BY/ 修定者	REV.DATE/ 修定日期	PART NO./ 料號	3882H	APPROVED BY/ 核准	
			MATERIAL/ 材質	PA66 UL 94V-0	CHECKED BY/ 審查	
			TREATMENT/ 表面處理		DRAWN/ 製圖	STONE
			CUSTOMER/ 客戶品名		DATE/ 製圖日期	2016-10-19
			UNIT/ 單位	mm	SCALE/ 比例	1:1
					DRAWING TYPE/ 圖面種類	