# 1.27x2.54mm Pin Header(Straight, Thru-Hole)

#### **HEADER PART NO:5994S**

#### **Features & Benefits**

- The series are ideal for board stacking applications
- Choice of two terminal lengths
- Notches for easy break-off
- Standoffs facilitate post soldering clean
- Also, we accept different various Type of specifications of Pin Header


## **Specification**


- Current Rating: 1Amp
- Insulation: 5000M  $\Omega$  Min.
- Dielectric Withstanding: 600V AC
- Contact Resistance:  $20m \Omega Max$ .
- Operating Temperature: 40°C to +105°C


### Materials (UL 94V-0)


- Contact Material: Phosphor Bronze
- Contact Plating: Gold/Tin over Nickel
- Insulation Material: Glass Filled Polyester











P.C. Board Hole Layout

# HO TIEN PRECISION INDUSTRY CO.,LTD. 合 田 精 密 工 業 股 份 有 限 公 司

RECORD OF REVISION / 修定內容	REV.BY / 修定者	REV. DATE / 修定日期	PART NO. / 型號		5994S		APPROVED BY / 核淮	
			METERIAL / 材質				CHECKED BY / 審查	
			TREATMENT/表面處理				DRAWN / 製圖	
			CUSTOMER / 客戶名稱				DATE/製圖日期	
			UNIT / 單位	mm	SCALE / 比例	1/4	DRAWING TYPE/圖面種類	