

Power Supply Connector Φ 2.0mm

Receptacle Housing (For Pin Connector)

HOUSING PART NO: LP

- Material: Nylon 66, UL 94V-0, UL 94V-2
- Pole: 1~4, 6, 9, 12, 15
- Pitch Between Poles: 6.20mm
- Accepts Housing: 3753F-BS-2

Specifications

- Voltage Rating: 300V AC, DC
- Contact Resistance: Initial value/10m Ω max.
After environmental testing/20m Ω
- Withstand Voltage: 1500V AC/minute
- Insulation Resistance: 1,000m Ω /min

	LP-01-6.9	300V-15A	LP-01-5.7	300V-15A	LP-02	300V-15A
	LP-03	300V-14A	LP-04-1	300V-13A	LP-04	300V-13A
	LP-06	300V-12A	LP-09	300V-9A	LP-12	300V-9A
					LP-15	300V-9A

HO TIEN PRECISION INDUSTRY CO., LTD.
合田精密工業股份有限公司

RECORD OF REVISION / 修定內容	REV.BY / 修定者	REV. DATE / 修定日期	PART NO. / 型號	LP	APPROVED BY / 核准
			MATERIAL / 材質		CHECKED BY / 審查
			TREATMENT / 表面處理		DRAWN / 製圖
			CUSTOMER / 客戶名稱		DATE / 製圖日期
			UNIT / 單位	mm	DRAWING TYPE / 圖面種類
			SCALE / 比例	1/13	