

Power Supply Connector $\text{\AA}2.0\text{mm}$

Receptacle Housing (For Pin Connector)

HOUSING PART NO: LR

- Material: Nylon 66, UL 94V-0, UL 94V-2
- Pole: 1~4, 6, 9, 12, 15
- Pitch Between Poles: 6.20mm
- Q' TY: 1,000 pcs/ bag
- Accepts Housing: 3753M-BS-2

Specifications

- Voltage Rating: 300V AC, DC
- Contact Resistance: Initial value/10m Ω max.
After environmental testing/20m Ω
- Withstand Voltage: 1500V AC/minute
- Insulation Resistance: 1,000m Ω /min

	<p>LR-01-6.9/LR-01-7.0 300V-15A</p>		<p>LR-02F 300V-15A</p> <p>LR-02 300V-15A</p>
	<p>LR-03 300V-14A</p>		<p>LR-04-01 300V-13A</p> <p>LR-04 300V-13A</p>
	<p>LR-06 300V-12A</p> <p>LR-09 300V-9A</p>	<p>LR-12 300V-9A</p>	<p>LR-15 300V-9A</p>

HO TIEN PRECISION INDUSTRY CO., LTD.
合田精密工業股份有限公司

RECORD OF REVISION / 修定内容	REV.BY / 修定者	REV. DATE / 修定日期	PART NO. / 型號	LR	APPROVED BY / 核准
			METERIAL / 材質		CHECKED BY / 審查
			TREATMENT / 表面處理		DRAWN / 製圖
			CUSTOMER / 客戶名稱		DATE / 製圖日期
			UNIT / 單位	mm	DRAWING TYPE / 圖面種類
			SCALE / 比例	1/13	